



Part Number: 10GB02

10GB Cat 6A Cable, U/UTP, LSZH, 4 Pair, AWG 23, Indoor CPR Eca

Product Description

Category 6A (500MHz), 4-Pair, U/UTP, Premise Horizontal Cable, 23 AWG Solid Bare Copper Conductors, Polyethylene Insulation, LSZH Jacket

Technical Specifications

Product Overview

Environmental Space:	Indoor - Euroclass Eca
Suitable Applications:	Horizontal and building backbone cable; Support current and future Cat. 6a and 6 applications such as; 10GBase-T (10 Gigabit Ethernet), 1000Base-T (Gigabit Ethernet), 100 Base-T, 10 Base-T, FDDI and ATM

Physical Characteristics (Overall)

Conductor

AWG	Material	No. of Pairs
23	BC - Bare Copper	4
Conductor Count:		8
Total Number of Pairs:		4
Conductor Size:		23 AWG

Insulation

Material	Nominal Diameter
Polyethylene	1.18 mm
Bonded-Pair:	No

Color Chart

Number	Color
Pair 1	White / Blue & Blue
Pair 2	White / Orange & Orange
Pair 3	White / Green & Green
Pair 4	White / Brown & Brown

Outer Shield Material

Type	Material
Foil	Special barrier tape

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
LSZH / FRNC	7.2 mm	0.3 mm

Construction and Dimensions

Min Elongation at Breakof Conductors:	10 %
Min Elongation at Breakof Insulation:	100 %

Cabling

Description
4 pairs twisted together + cross web of polyolefin + overlapping polyester foil over cable core

Min Elongation at Breakof Jacket:	100 %
Min Tensile Strength of Jacket:	9 MPa

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max DCR Unbalanced Between Pairs [%]	Max. DCR Unbalanced Within Pair [%]
95 Ohm/km	4 %	2 %

Capacitance

Max. Capacitance Unbalanced Pair to Pair	Max. Mutual Capacitance
1,600 pF/m	56 pF/m

Delay

Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
45 ns/100m	67 %

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Min. PSANEXT	Min. PSAACRF	Min. TCL [dB]	Min. ELTCTL [dB]
1 MHz	2.1 dB/100m	75.3 dB	72.3 dB	73.2 dB	70.2 dB	68 dB	65.0 dB	20 dB	67.0 dB	67.0 dB	40 dB	35 dB
4 MHz	3.8 dB/100m	66.3 dB	63.3 dB	62.5 dB	59.5 dB	56 dB	53.0 dB	23 dB	67.0 dB	66.2 dB	34 dB	23 dB
10 MHz	5.9 dB/100m	60.3 dB	57.3 dB	54.4 dB	51.4 dB	48 dB	45.0 dB	25 dB	67.0 dB	58.2 dB	30 dB	15 dB
16 MHz	7.5 dB/100m	57.2 dB	54.2 dB	49.8 dB	46.8 dB	43.9 dB	40.9 dB	25 dB	67.0 dB	54.1 dB	28 dB	10.9 dB
31.2 MHz	10.5 dB/100m	52.9 dB	49.9 dB	42.4 dB	39.4 dB	38.1 dB	35.1 dB	23.6 dB	67.0 dB	48.3 dB	25.1 dB	5.1 dB
62.5 MHz	15 dB/100m	48.4 dB	45.4 dB	33.4 dB	30.4 dB	32.1 dB	29.1 dB	21.5 dB	65.6 dB	42.3 dB	22 dB	
100 MHz	19.1 dB/100m	45.3 dB	42.3 dB	26.2 dB	23.2 dB	28 dB	25.0 dB	20.1 dB	62.5 dB	38.2 dB	20 dB	
125 MHz	21.5 dB/100m	43.8 dB	40.8 dB	22.3 dB	19.3 dB	26.1 dB	23.1 dB	19.4 dB	61.0 dB	36.3 dB	19 dB	
200 MHz	27.6 dB/100m	40.8 dB	37.8 dB	13.2 dB	10.2 dB	22 dB	19.0 dB	18 dB	58.0 dB	32.2 dB	17 dB	
250 MHz	31.1 dB/100m	39.3 dB	36.3 dB	8.3 dB	5.3 dB	20 dB	17.0 dB	17.3 dB	56.5 dB	30.2 dB	16 dB	
300 MHz	34.3 dB/100m	38.1 dB	35.1 dB	3.9 dB	0.9 dB	18.5 dB	15.5 dB	17.3 dB	55.3 dB	28.7 dB		
500 MHz	45.3 dB/100m	34.8 dB	31.8 dB	-10.4 dB	-13.4 dB	14 dB	11.0 dB	17.3 dB	52.0 dB	24.2 dB		

Segregation class according EN50174-2:	b
--	---

Current

Max. Recommended Current [A]
1.5 A

Voltage

Voltage Rating [V]
Max. 72 V DC

Temperature Range

Installation Temp Range:	0°C To +50°C
Operating Temp Range:	-30°C To 60°C

Mechanical Characteristics

Bulk Cable Weight:	50 kg/km
Max Recommended Pulling Tension:	110 N

Standards

ISO/IEC Compliance:	ISO/IEC 11801 Ed. 2.2:2002/A2:2010/C1:2011
CPR Euroclass:	Eca
CENELEC Compliance:	EN 50173-1 Ed. 3:2011
Data Category:	Category 6A
ANSI Compliance:	ANSI/TIA 568.2-D (2018)
IEEE Specification:	PoE: IEEE 802.3bt Type 1, Type 2, Type 3, Type 4

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	2015-08-24
---------------------------------------	------------

Flammability, LS0H, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-1-2
Burning Load:	550 kJ/m
Amount of Halogen acc. to IEC 60754-1 & EN50267-1:	Zero

Part Number

Variants

Item #	Color	Length
10GB02.0B305	Blue	305 m
10GB02.0B500	Blue	500 m
10GB02.0B100	Blue	100 m
10GB02.0G305	Gray	305 m
10GB02.0G500	Gray	500 m
10GB02.0G100	Gray	100 m
10GB02.0P305	Purple	305 m
10GB02.0P500	Purple	500 m
10GB02.0P100	Purple	100 m
10GB02.0W305	White	305 m
10GB02.0W500	White	500 m

Patent:	h
---------	---

History

Update and Revision:	Revision Number: 0.001 Revision Date: 31-03-2024
----------------------	--

© SIGMA net

All Rights Reserved.

Although Sigma makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Sigma provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Sigma be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Sigma has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Sigma products are subject to Sigma's standard terms and conditions of sale.

Sigma believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Sigma's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.