



Product: 5300SG

Security & Sound, 2 Conductor 18 AWG, BC, Shielded, CMR

Product Description

Security & Commercial Audio Cable, Riser-CMR, 2-18 AWG stranded bare copper conductors with polypropylene insulation, Beldfoil® shield and PVC jacket with ripcord

Technical Specifications

Product Overview

Suitable Applications:	Intercom/PA Systems, Sound/Audio Systems
------------------------	--

Construction Details

Conductor

Element	Number of Element	AWG	Stranding	Material
Conductor(s)	2	18	7x26	BC - Bare Copper

Insulation

Element	Material	Thickness [in]	Color Code
Conductor(s)	PP - Polypropylene	0.0085	Black, Red

Outer Shield Material

Type	Material	Coverage	Drainwire Type
Tape	Alum / Poly	100%	24 AWG (7x32) TC

Outer Jacket Material

Material	Thickness	Diameter	Ripcord
PVC - Polyvinyl Chloride	0.017 in	0.162 in	Yes

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
"Conductor(s)"	6.5 Ohm/1000ft	53 pF/ft	95.5 pF/ft	5 Amps per Conductor at 25°C

Voltage

UL Voltage Rating
300 V (CMR)

Mechanical Characteristics

Temperature

UL Rating	Operating
75°C	-20°C to +75°C

Bend Radius

Stationary Min.
1.75 in

Max. Pull Tension:	57.5 lbs
Bulk Cable Weight:	18 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Fire Resistance:	UL1666 Vertical Shaft, FT4, IEC 60332-1-2
NEC / UL Compliance:	Article 800, CMR
CEC / C(UL) Compliance:	CMG
CPR Euroclass:	Eca
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Date: 06-03-2024
----------------------	---------------------------

© SIGMA net
All Rights Reserved.

Although Sigma makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Sigma provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Sigma be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Sigma has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Sigma products are subject to Sigma's standard terms and conditions of sale.

Sigma believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Sigma's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.